
Horizontal Directional Drilling Cost Per Foot

*Horizontal
Directional
Drilling Cost
Per Foot*

*Downloaded
from
evoluir.abar.org.br
by Whitney &
Jada*

UNDERSTANDING HORIZONTAL DIRECTIONAL DRILLING COST PER FOOT

When you need to install underground utilities such as water lines, gas pipes, electrical conduits, or fiber optic cables, **horizontal directional drilling (HDD)** has become the go-to method for minimizing surface disruption. Unlike

traditional open-cut trenching, HDD allows you to bore under roads, rivers, landscaping, and existing infrastructure. However, one of the most pressing questions for project planners and homeowners alike is: **What is the horizontal directional drilling cost per foot?**

The answer is not a simple flat rate. The cost per foot for directional drilling can vary dramatically based on a multitude of factors, ranging from

soil conditions to pipe diameter.

Understanding these variables is essential for accurate budgeting and project planning. In this article, we will break down everything that influences the price of HDD, provide typical cost ranges, and offer practical advice on managing your drilling budget.

WHAT IS HORIZONTAL DIRECTIONAL DRILLING?

Horizontal directional drilling is a trenchless construction method used to install pipes, cables, and conduit underground along a predetermined bore path. A drilling rig is positioned at the surface, and a steerable drill head creates a small pilot hole. Once the pilot

hole reaches the exit point, a reamer is pulled back to enlarge the hole to the required diameter, simultaneously pulling the product pipe into place.

Because HDD avoids digging a trench, it preserves surface features, reduces restoration costs, and minimizes

environmental impact. However, the specialized equipment and expertise required mean that the

horizontal directional drilling cost per foot is typically higher than simple trenching for short, straight runs — but often lower overall when you factor in restoration and disruption.

AVERAGE

DIRECTIONAL DRILLING COST

PER FOOT

While every project is unique, industry data provides a useful starting point. In the United States, **horizontal directional drilling costs** generally range from **\$5 to \$30 per foot** for small to medium-diameter installations. For larger diameter pipes or challenging conditions, costs can exceed \$100 per foot. Below is a general breakdown based on pipe diameter:

- **2 to 4 inch diameter:** \$5 - \$15 per foot
- **6 to 8 inch diameter:** \$12 - \$25 per foot
- **10 to 14 inch diameter:** \$20 -

HORIZONTAL \$50 per foot

- **16 inch and larger:** \$50 - \$150+ per foot

These figures include the drilling process itself but may not include additional costs such as mobilization, site preparation, pipe materials, or restoration. Always request a detailed quote that breaks down the **directional drilling price per foot** for your specific location.

KEY FACTORS THAT INFLUENCE HORIZONTAL DIRECTIONAL DRILLING COST PER FOOT

1. Soil

and

recommended to avoid unexpected expenses.

2. Bore Length Condition

s

and

Depth

Soil type has a direct impact on drilling difficulty and therefore on cost. **Soft, sandy soils** are easier to bore through, resulting in lower costs per foot. **Clay soils** can be moderately difficult, while **rocky or cobble-filled ground** significantly increases wear on drill bits and slows progress. Hard rock may require special tooling and even rock-reaming, pushing the **HDD cost per foot** to the higher end of the spectrum. A geotechnical survey before drilling is

Longer bores often benefit from economies of scale — the mobilization cost is spread over more feet, potentially lowering the per-foot rate. However, extremely long bores (over 1,000 feet) can require larger rigs and more sophisticated guidance systems, increasing cost. Depth also matters: shallow bores (4-10 feet deep) are generally cheaper per foot than deeper bores (20+ feet) because deeper drilling requires more powerful

equipment and higher mud pressures to stabilize the hole.

3. Pipe Material and Diameter

The type of pipe you install affects the overall project cost.

High-density polyethylene (HDPE) is the most common material for HDD because it is flexible and can be fused into long strings. Steel or ductile iron pipes are heavier and more expensive to handle. Larger diameter pipes require larger reamers, more drilling fluid, and more powerful rigs, all of which increase the **directional boring**

cost per foot. For example, drilling for a 4-inch gas line is far cheaper than pulling a 16-inch water main.

4. Location and Accessibility

Geographic location plays a major role. Projects in urban areas with heavy traffic, limited space, and strict permitting requirements will have higher costs than rural installations. Similarly, drilling under highways, railways, or rivers may require additional engineering studies and safety measures, raising the

per-foot price. Remote or difficult-to-access sites increase mobilization fees, which can be a significant portion of the total cost.

5. Crew Size and Equipment

Experienced HDD crews command higher hourly rates, but they also work faster and with fewer errors. The size of the drilling rig also matters: mini rigs for small residential jobs cost less to operate than maxi rigs for large-diameter bores. A typical crew for a medium-sized project includes an operator, a locator, a

drill hand, and possibly a superintendent. Labor costs are usually factored into the **underground boring cost per foot**.

6. Drilling Fluid Requirements

Bentonite-based drilling fluids are used to stabilize the borehole, cool the drill bit, and transport cuttings. In sandy or collapsing soils, more fluid is needed, and disposal of spent mud can add expense. If the project requires environmentally friendly additives or special fluid recycling, costs per foot may increase.

7. Obstacles and Existing Utilities

Every utility line, pipe, or fiber optic cable encountered along the bore path adds risk and complexity. Locating and avoiding existing infrastructure requires potholing, ground penetrating radar, or vacuum excavation. If an accidental strike occurs, repair costs can be enormous. For this reason, careful utility mapping before drilling is essential and adds to the overall **HDD price per foot.**

8. Permittin g and Environm ental Regulatio ns

Many jurisdictions require permits for directional drilling, especially when crossing public roads, waterways, or environmentally sensitive areas. Permit fees, environmental impact assessments, and bonding requirements all contribute to the total project cost. In some regions, these costs

can add several thousand dollars to the job, effectively increasing the per-foot rate.

ADDITIONAL COSTS BEYOND THE PER-FOOT RATE

When comparing quotes, it is crucial to understand what is included in the stated **horizontal directional drilling cost per foot**. Many contractors quote only the drilling and pipe pulling, leaving out these common additional expenses:

- **Mobilization/De mobilization:** Bringing the rig and support trucks to your site can cost \$500 to \$5,000 or more, depending on

distance and rig size.

- **Site**

- **Preparation:**

- Clearing the work area, setting up temporary fencing, and protecting existing surfaces.

- **Potholing:**

- Exposing existing utilities to confirm their location — typically \$300–\$500 per hole.

- **Pipe Fusion or Welding:**

- For HDPE pipe, heat fusion is required; for steel, welding. This adds labor and material costs.

- **Restoration:**

- Replacing topsoil, sod, asphalt, or

concrete disturbed during the job. Trenchless methods minimize restoration, but entry/exit pits still need repair.

Always ask for a complete line-item estimate to compare apples to apples.

HORIZONTAL DIRECTIONAL DRILLING VS. TRENCHING COSTS

One common question is how HDD compares to traditional open-cut trenching in terms of cost per foot. For a simple straight run in soft soil with no obstacles, trenching can be cheaper — typically \$4 to \$12 per foot depending on depth and pipe size. However, trenching

costs skyrocket when you factor in pavement removal, traffic control, landscaping restoration, and the cost of repairing driveways or sidewalks. In urban environments, HDD often becomes the more economical choice overall, even with a higher per-foot drilling rate.

For example, trenching a 100-foot line across a busy street could cost thousands in permits, traffic management, and repaving. HDD can drill under the same street with minimal surface disruption, often for a similar or lower total project cost. That is why **directional drilling rates per foot** are more competitive than they initially appear.

ACCURATE HDD COST ESTIMATE

To obtain a realistic **horizontal directional drilling price per foot** for your project, follow these steps:

1. **Provide clear details:** Pipe diameter, material, length of bore, and known soil conditions.
2. **Mark the bore path:** Clearly define entry and exit points and note any obstacles (trees, roads, buildings, utilities).
3. **Obtain multiple quotes:** Get at least three bids from reputable directional drilling contractors in

your area.

4. Ask for a breakdown:

Request itemized costs for mobilization, drilling, pipe, fluid, and restoration.

5. Check credentials:

Ensure the contractor is licensed, insured, and experienced with similar projects.

Remember that the cheapest quote may not be the best value. Inexperienced crews can cause costly mistakes, such as stuck pipes or surface heave, which lead to expensive repairs and delays.

TIPS TO REDUCE YOUR

DIRECTIONAL DRILLING COSTS

While you cannot control all factors, there are ways to keep the **HDD cost per foot** under control:

- **Combine multiple utilities in one bore:** Running water, gas, and electric together in one conduit reduces overall cost.
- **Choose the right pipe material:** HDPE is often more economical than steel for most applications.
- **Optimize bore path:** A straight, simple route is far cheaper than one with curves or steep angles.
- **Schedule during off-peak**

times: Some contractors offer lower rates during slower seasons.

- **Prepare the site yourself:** Clearing vegetation and marking utility lines can reduce the contractor's setup time.
- **Use local contractors:** They avoid long-distance mobilization fees and know local soil conditions.

CONCLUSION

Horizontal directional drilling cost per foot is influenced by a wide range of variables including soil type, bore length, pipe diameter, site accessibility, and local regulations. While

average rates fall between \$5 and \$30 per foot for many common projects, larger or more complex bores can cost significantly more. The true value of HDD lies not just in the per-foot drilling price but in the substantial savings from reduced surface restoration, minimal traffic disruption, and lower environmental impact. When evaluating your next underground installation, consider the total project cost — not just the boring rate — and always work with an experienced contractor who can provide a transparent, detailed estimate. By understanding the factors that affect pricing, you can make an informed decision, stay within budget, and ensure a successful, disturbance-free installation.