
Kubota Battery Cross Reference

*Downloaded
from
Kubota evoluir.abar.org.br
Battery Cross by Becker &
Reference Valentina*

UNDERSTANDING THE KUBOTA BATTERY CROSS REFERENCE: A COMPLETE GUIDE FOR EQUIPMENT OWNERS

When your Kubota tractor, lawn mower, or compact excavator refuses to start on a cold morning, the battery is often the culprit. For owners and mechanics alike, finding the right replacement can be confusing due to the sheer number of OEM

part numbers, group sizes, and aftermarket options available. This is where a Kubota battery cross reference becomes an indispensable tool. Rather than blindly purchasing a battery from a dealer and paying a premium, you can use a cross reference to identify compatible, often more affordable, alternatives without sacrificing performance or reliability. In this comprehensive guide, we will explore everything you need to know about cross referencing Kubota batteries, from

understanding specifications to selecting the best replacement for your specific machine.

WHAT IS A KUBOTA BATTERY CROSS REFERENCE?

A Kubota battery cross reference is a systematic comparison between original equipment manufacturer (OEM) battery part numbers and aftermarket equivalents from leading battery brands. Kubota, like many equipment manufacturers, sources batteries from various suppliers and assigns their own part numbers. These numbers often correspond to industry-standard battery group sizes and specifications such as cold cranking

amps (CCA), reserve capacity (RC), voltage, and terminal placement. By using a cross reference chart or database, you can identify which aftermarket battery fits and performs just as well as the original, often at a lower cost.

Why OEM Part Numbers Can Be Misleading

Kubota uses numerous part numbers for batteries across different models and production years. For example, a battery

used in a BX series tractor may have a completely different part number than one used in an L series, even if both batteries are physically similar. Without a cross reference, you might assume that only the Kubota-branded battery with the exact number will work. In reality, many aftermarket batteries—such as those from Interstate, Exide, Optima, or Yuasa—offer identical or superior specifications. The key is matching not just the physical dimensions but also the electrical characteristics and terminal orientation.

KEY BATTERY SPECIFICATIONS TO UNDERSTAND

Before diving into specific cross

references, it is essential to understand the technical specifications that define a battery's suitability for your Kubota equipment. A cross reference is only useful if you know what these numbers mean.

- **Voltage:** Nearly all Kubota equipment uses a 12-volt electrical system, though some older models may use 6-volt systems. Always verify the voltage before purchasing.
- **Cold Cranking Amps (CCA):** This measures the battery's ability to start an engine in cold temperatures. Higher CCA is generally better, especially for

diesel engines that require more cranking power. A typical Kubota compact tractor may require between 350 and 650 CCA.

- **Cranking Amps (CA):** Similar to CCA but measured at 32°F instead of 0°F. This number is typically higher than CCA and is more relevant in warmer climates.
- **Reserve Capacity (RC):** The number of minutes a battery can deliver a constant load (usually 25 amps) before dropping below a usable voltage. This is important for equipment

with lights, hydraulic pumps, or other electrical accessories.

- **Group Size:** This industry-standard designation defines the physical dimensions, terminal placement, and polarity. Common group sizes for Kubota equipment include U1, 22NF, 24, 27, 31, and 4D.
- **Terminal Type:** Batteries come with top posts, side posts, or a combination. Kubota equipment typically uses top-post batteries, but some models

require stud terminals or specific adapters.

COMMON KUBOTA EQUIPMENT AND THEIR BATTERY PART NUMBERS

To make a proper Kubota battery cross reference, you first need to identify your machine's OEM part number. Below are some common Kubota models and their typical battery part numbers. Note that production changes may alter these numbers, so always confirm with your owner's manual or a dealer lookup.

Kubota Compact

and Sub-Compact Tractors

The B, BX, and L series are among the most popular Kubota tractors for homeowners and small farms. These machines often use batteries from group sizes U1 or 22NF.

- **BX1850, BX2350, BX2660:** OEM part numbers often include 66800-53160 or 66700-5316A. A common cross reference is the Interstate U1-3 or Exide U1-AGM, both providing approximately 340 CCA.
- **B2320, B2620,**

B2920: These models typically use a group size 22NF battery. OEM numbers like 66100-53161 cross to Interstate 22NF-AGM or Odyssey PC925T.

- **L2501, L3200, L3800, L3901, L4701:** These larger compact tractors require more cranking power. OEM part number 66800-53160 or 66700-5316A crosses to group size 24 or 27 batteries. Interstate 24-72 or Optima 8020-164 are popular options.

Kubota Lawn Mowers and Zero- Turn Riders

Kubota's ZD and ZG series zero-turn mowers, as well as their T series lawn tractors, often use smaller batteries. However, some commercial models require high-CCA batteries due to heavier electrical loads.

- **ZD1211, ZD221, ZD326:** These zero-turn mowers frequently use a

U1 battery. OEM part number 66700-5316A crosses to Exide U1-AGM or Yuasa YB14L-A2.

- **ZG123, ZG124, ZG227:** These models may use group size 22NF or U1 depending on the year. Always check the existing battery or manual.
- **T1870, T2080, T2290:** Lawn tractors in this series typically use a group size U1 battery with 300-400 CCA.

Kubota Excavators and

Construction Equipment

Kubota's KX, U, and SVL series mini excavators and skid steers often require larger, more powerful batteries. These machines operate in demanding conditions and need reliable starting power.

- **KX41, KX71, KX91:** These mini excavators typically use group size 24 or 27 batteries. OEM part numbers like 66800-53160 cross to Interstate 24-72 or Motorcraft

CHART

- **SVL65, SVL75, SVL90:** Compact track loaders require group size 31 batteries for high CCA and reserve capacity. OEM number 66700-5316B crosses to Odyssey 31-PC2150 or Optima D31T.
- **U17, U25, U35:** These ultra-compact excavators often use a group size 22NF or U1 battery. Cross references include Yuasa YIX30L and Interstate 22NF-MF.

HOW TO USE A KUBOTA BATTERY CROSS REFERENCE

You can find Kubota battery cross reference charts online from battery manufacturers, equipment dealers, or specialty automotive retailers. Here is a step-by-step approach to using them effectively.

1. **Locate your OEM part number:** Check the current battery in your machine for a Kubota part number, or consult your owner's manual. The number is usually printed on the battery label or stamped into the case.
2. **Identify the group size:** If the OEM number is not available, measure the

battery length, width, and height, and note the terminal type and location. Use a group size chart to find the corresponding size.

3. **Check CCA and RC**

requirements:

Your owner's manual specifies minimum CCA and RC. A cross reference should list batteries that meet or exceed these values.

4. **Select an aftermarket brand:**

Compare options from reputable manufacturers. Interstate, Exide, Optima, Odyssey, Yuasa, and Deka all offer high-quality batteries suitable

for Kubota equipment.

5. **Verify terminal orientation:**

Positive and negative terminal positions must match your cables. A battery that is too long or has reversed terminals may not fit or could cause a short circuit.

**BATTERY TYPES:
WHICH ONE IS
RIGHT FOR YOUR
KUBOTA?**

Not all batteries are created equal. When performing a Kubota battery cross reference, you will encounter several different battery chemistries and constructions. Understanding the

differences helps you choose the best option for your usage pattern.

Flooded Lead-Acid Batteries

These are the most common and affordable option. They contain liquid electrolyte and require periodic maintenance such as checking water levels and cleaning corrosion. For occasional use tractors and mowers, a quality flooded battery offers good value. Examples include Interstate 24-72 and Exide 24-500.

AGM

(Absorbent Glass Mat) Batteries

AGM batteries are sealed, maintenance-free, and resistant to vibration—a major advantage for off-road equipment. They offer higher CCA per size and longer lifespan than flooded batteries. AGM is an excellent choice for Kubota tractors and excavators that operate on rough terrain. Popular AGM options include Odyssey PC925T, Optima D31T, and Interstate 22NF-AGM.

Gel Cell Batteries

Gel batteries are also sealed and maintenance-free, but they use a silica gel electrolyte. They are less common in Kubota equipment due to their lower CCA output and sensitivity to overcharging. However, they perform well in deep-cycle applications. Not generally recommended for primary starting use in tractors.

Lithium-Ion Batteries

Lithium-ion starting batteries are emerging

in the equipment market. They are significantly lighter, last longer, and offer high CCA in a small package. However, they are expensive and require a compatible charging system. Some Kubota owners choose lithium for weight reduction or extreme cold weather performance, but they are not a direct cross reference for most OEM applications without modifications.

WHERE TO FIND RELIABLE CROSS REFERENCE INFORMATION

Several resources can help you identify the correct Kubota battery cross reference for your machine. Always verify information from multiple sources to avoid costly mistakes.

- **Battery manufacturer websites:**

Interstate, Exide, and Odyssey offer online lookup tools where you can enter OEM part numbers or equipment models. These tools are generally accurate and up to date.

- **Kubota dealer parts departments:**

Your local dealer can provide OEM part numbers and sometimes recommend aftermarket alternatives. However, they may not endorse non-OEM brands.

- **Online forums and communities:**

Kubota owner forums like OrangeTractorTalks and TractorByNet have extensive discussions about battery replacements. Experienced owners often share their successful cross references.

- **Automotive parts retailers:**

Websites like BatteryMart, Amazon, and Summit Racing allow you to filter by group size and specifications. Reading customer reviews for your specific Kubota model can be very helpful.

TIPS FOR YOUR CROSS- REFERENCED

BATTERY

Once you have selected the correct replacement using a Kubota battery cross reference, proper installation ensures safety and long life. Follow these guidelines.

- **Disconnect the negative terminal first:**

Always remove the negative (black) cable before the positive (red) to minimize the risk of short circuits.

- **Clean the tray and terminals:**

Remove any corrosion or debris from the battery tray and

INSTALLATION

cable ends. Use a wire brush and a baking soda solution to neutralize acid.

- **Secure the battery:** Use the factory hold-down bracket or a universal strap to prevent movement. Vibration can damage internal plates and shorten battery life.
- **Apply anti-corrosion spray:** After connecting the terminals, spray them with a battery terminal protector or coat them with dielectric grease.
- **Reconnect positive first, then negative:** Reverse the removal order to

- avoid sparks.
- **Test the system:** Start the engine and verify that the charging system is functioning. A healthy alternator